



Item # _____

Job _____

METRO CASE CARTS

The functional design of Metro Case Carts maximize usable inside space for handling storage and transport tasks efficiently. Carts can be used wherever contents must be protected from an “unclean” environment, including free-standing ambulatory care centers, surgi-centers, and hospital based or out-patient surgeries.

- **Accessible:** Wire roller shelf extends out half way, easily and quietly, even at lowest level where accessibility is vital. Also available in solid or wire without roller.
- **Efficient:** Brackets, which hold shelves, attach and detach quickly from “keyhole” slots for easy shelf adjustability at 2” increments.
- **Easily Maneuverable:** Full length handles on both sides of the low profile carts and CASE-H36 allow for pushing or pulling from either end and provide better cart control. One full length handle is ergonomically located on the CASE-H24 cart.
- **Independent Caster Channel System:** A separate caster channel on each side of the cart means having to replace only one caster channel should a damaging

situation occur. With competitive models, the entire dolly would have to be replaced, given the same situation.

- **Durable:** Double-panel door construction offers better strength and minimizes maintenance. Stainless steel cabinet and optional shelves have “safety edges” to eliminate ripping of packs.
- **Cleans Easily:** Stainless steel construction makes units cart washable. Shelves and brackets remove for washing. Weep hole at the cart’s front corners and underside of door panels facilitate drainage and drying.
- **High-Profile Model Available:** The high-profile models (CASE-H24, CASE-H36) save floor space, as compared to conventional case carts. The vertical design eliminates “stooping” and offers quick, easy “stand-up” access to most contents.
- **Choice of Casters:** Metro case carts are available with either stainless steel casters or maintenance free polymer casters. Both are non-corrosive and cart-washable. The polymer caster also provide a swivel lock as a standard feature.





METRO CASE CARTS

Specifications

- **Cart:** Type 304 Stainless Steel, No. 3 finish type.
- **Shelves:** Stainless Steel, wire (with or without roller) or solid, sold separately.
- **Bumper:** Replaceable stand-out wraparound with reinforced corners
- **Custom Orders:**
 - Extended tops for use as a back table
 - Tote boxes
 - Carts modified for elevator coupler systems
 - Carts modified for mobile assist devices.
 - Custom sizes or design
 - Over-the-road models
 - Security seal lock on doors
 - Various caster options
- **Casters:**
 - Stainless Steel: one swivel lock, two swivel with brake, one swivel on 48" model; three swivel, one swivel with brake on other models.
 - Polyurethane wheels and stainless steel horn
 - All stainless steel hardware and top plate
 - Zerk fittings
 - 5" (127mm) diameter, 1 $\frac{1}{2}$ " (38mm) face (NOTE: CASE-H36 equipped with 6" (152mm) diameter, 1 $\frac{1}{2}$ " face casters).
 - Grease sealed bearings
 - Polymer: one swivel lock, two swivel with brake, one swivel on all models.
 - Advantage Thermal Plastic Rubber wheels and reinforced nylon horn
 - All stainless steel hardware and top plate
 - Zerk fittings
 - 5" (127mm) diameter, 1 $\frac{1}{4}$ " (32mm) round face (NOTE: CASE-H36 equipped with 6" (152mm) diameter, 1 $\frac{1}{2}$ " face casters).

Dimensions

Case Carts (shelves sold separately)

	Width		Overall		Height		Approx. Pkd. Wt.		Cat. No. with Stainless Casters	Cat. No. with Polymer Casters	
	Overall (in.)	(mm)	Cabinet (in.)	(mm)	Overall (in.)	(mm)	Cabinet (in.)	(mm)			(lbs.)
32 $\frac{7}{8}$ "	835	28 $\frac{1}{2}$ "	724	38 $\frac{1}{4}$ "	972	28 $\frac{1}{2}$ "	724	115	52.27	CASE-L24	CASE-L24P
44 $\frac{7}{8}$ "	1140	28 $\frac{1}{2}$ "	724	38 $\frac{1}{4}$ "	972	28 $\frac{1}{2}$ "	724	186	84.5	CASE-L36	CASE-L36P
56 $\frac{7}{8}$ "	1445	28 $\frac{1}{2}$ "	724	38 $\frac{1}{4}$ "	972	28 $\frac{1}{2}$ "	724	212	96.4	CASE-L48	CASE-L48P
32 $\frac{7}{8}$ "	835	28 $\frac{1}{2}$ "	724	57 $\frac{1}{8}$ "	1451	46 $\frac{1}{2}$ "	1181	162	73.6	CASE-H24	CASE-H24P
44 $\frac{7}{8}$ "	1140	28 $\frac{1}{2}$ "	724	58 $\frac{1}{8}$ "	1476	46 $\frac{1}{2}$ "	1181	262	118.8	CASE-H36	CASE-H36P

All units are 28 $\frac{1}{2}$ " (724mm) deep overall. Cabinet depth is 25 $\frac{1}{2}$ " (648mm).

Optional Shelves (wire pullout, wire pullout with rollers, solid)

Cart	Shelf Size		Approx. Pkd. Wt. (with 2 brackets)		Cat. No. Wire Shelf	Approx. Pkd. Wt. (with 2 brackets)		Cat. No. Roller Shelf	Approx. Pkd. Wt. (with 2 brackets)		Cat. No. Solid Shelf
	(in.)	(mm)	(lbs.)	(kg)		(lbs.)	(kg)		(lbs.)	(kg)	
CASE-L24(P)	24x24	610x610	9	4.1	CCWS-24	12	5.5	CCROLWS-24	15	6.8	CCSS-24
CASE-L36(P)	24x36	610x914	13	5.9	CCWS-36	16	7.3	CCROLWS-36	19	8.6	CCSS-36
CASE-L48(P)	24x48	610x1219	19	8.6	CCWS-48	21	9.5	CCROLWS-48	25	11.3	CCSS-48
CASE-H24(P)	24x24	610x610	9	4.1	CCWS-24	12	5.5	CCROLWS-24	15	6.8	CCSS-24
CASE-H36	24x36	610x914	13	5.9	CCWS-36	16	7.3	CCROLWS-36	19	8.6	CCSS-36

Each shelf includes two attachment brackets.