



Item # \_\_\_\_\_

Job \_\_\_\_\_

## LINEN TRUCK CLT SERIES

- **Versatile Construction:** By positioning the two folding shelves on the CLT – either horizontally or vertically – three different truck configurations become possible:
  - #1. Folding shelves can be positioned horizontally for easy transport and accessibility for fresh linen. (35-40-bed capacity)
  - #2. Folding shelves can be positioned vertically to become an enclosure panel, creating a spacious rolling bin for the collection and the transportation of soiled linen.
  - #3. While folding shelves are in a vertical position, the lower folding shelf can be flipped out and up, enabling contents to be unloaded with a minimum amount of handling.

**Note:** See illustrations on back.
- **Open Wire Features:** Minimize dust accumulation and allow a free circulation of air, greater visibility of stored items and greater light penetration.
- **Brake Lock/Swivel Lock Combination Casters:** Enable a single pair of casters to serve as swivel, rigid or brake casters to meet varying operational needs. See sheet #11.70.
- **Covers Available:** Catalog numbers on reverse side. See sheet #11.80.
- **Pitched Aluminum Dust Cover:** Shields lower truck contents against dust or dirt.
- **Cart-Washable**



### Heavy-Duty

*Heavy-duty models contain heavier gauge corner posts and two additional intermediate frames.*



### Standard-Duty



# LINEN TRUCK CLT SERIES

## Dimensions

Model No.	Description	Shelf Size				Height	
		Width (in.)	Width (mm)	Length (in.)	Length (mm)	(in.)	(mm)
<b>STANDARD-DUTY CHROME</b>							
CLTS2460C	CLT with 3-sided top frame	24	610	60	1524	70	1775
CLTS2448C	CLT with 3-sided top frame	24	610	48	1219	70	1775
<b>STANDARD-DUTY - STAINLESS STEEL</b>							
CLT2460S	CLT with 3-sided top frame	24	610	60	1524	70	1775
<b>HEAVY-DUTY - CHROME</b>							
CLTH2460C	CLT with 3-sided top frame	24	610	60	1524	70	1775

**Material:** Chrome Models: chrome-plated steel dolly and aluminum tubes. Stainless Steel: stainless steel dolly and aluminum tubes.

**Note 1:** Casters on above units consist of two 6P and one pair BL6P, 8P and BL8P available on special order.

**Note 2:** Before employing any of various cart-washing systems, please contact InterMetro representative for special recommendations on casters and for cleaning instructions.

## Accessories

### UNCOATED COVERS

Width		Length		Height		Zippered Closure	Velcro Closure
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	Cat. No.	Cat. No.
24	610	48	1219	62	1575	24x48x62UC	24x48x62VUC
24	610	60	1524	62	1575	24x60x62UC	24x60x62VUC

### COATED COVERS

Width		Length		Height		Zippered Closure	Velcro Closure
(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	Cat. No.	Cat. No.
24	610	48	1219	62	1575	24x48x62C	24x48x62VC
24	610	60	1524	62	1575	24x60x62C	24x60x62VC