



Item# \_\_\_\_\_

Job \_\_\_\_\_



## METRO™ CONDUCTIVE STEM CASTERS

- **Metro Conductive Stem Casters** are designed to fit Super Erecta Shelf® posts to form shelf carts and other mobile units.
- **Reliable:** All Metro Conductive Casters conform to Federal Specification FF-C-88C regarding the acceptable standards for conductive wheels.
- **Cart Washable:** Metro's conductive casters have grease seals and zerk fittings. Can withstand high pressure washings.
- **Styles Available:** Swivel, foot-operated brake, and rigid casters available in conductive material.
- **Donut Bumpers:** Standard on all conductive casters.
- **Additional Caster Types Available**

Job \_\_\_\_\_



# METRO™ CONDUCTIVE STEM CASTERS

## DIMENSIONS Conductive Casters — Stem-Type:

Model	Type	Wheel Dia.		Face		Load Rating		Weight Ea.	
		(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	(lbs.)	(kg)
5MC	Stem/Swivel	5	127	1 1/4	32	175	79	2 1/2	1.1
5MBC	Stem/Brake	5	127	1 1/4	32	175	79	2 3/4	1.2
5MRC	Stem/Rigid	5	127	1 1/4	32	175	79	3 1/2	1.6

Brakes are foot-operated

**NOTE 1:** To insure proper conductivity: 1) aluminum split sleeves must be used with each shelf  
2) casters must be maintained according to provided instructions.

**NOTE 2:** Stem casters are shipped with donut bumper **at no extra charge.**

**NOTE 3:** Rigid casters are held in position by a connecting channel. When ordering rigid casters shelf width must be known.

**NOTE 4:** Load Height for all 5M conductive casters — 6 1/2" ± 1/16" (155 ± 1.5mm).

## Posts for Stem Casters:

Height		Approx. Pkd. Wt.		Model No.	Model No.
(in.)	(mm)	(lbs.)	(kg)	Plated	Stainless
33 7/8	861	2	0.9	33UP	33UPS
54	1370	3	1.4	54UP	54UPS
62	1575	3 1/2	1.6	63UP	63UPS
74	1880	4	1.8	74UP	74UPS
86	2185	5	2.3	86UP	86UPS

These posts come without leveling bolt to accommodate stem casters.