



TIM CAMPBELL 800-400-7500


Item # \_\_\_\_\_

Job \_\_\_\_\_

## Metro® BOW-TIE™ DUNNAGE RACKS with \*Microban® Antimicrobial Product Protection

***Metro Bow-Tie Dunnage Racks with built-in Microban® antimicrobial product protection are protected from bacteria, mold, mildew and fungi that cause odors, stains and product degradation.***

- **Easy to Clean:** Smooth rotomolded polymer offers snag-free surfaces and promotes easy cleaning. Microban® antimicrobial product protection keeps dunnage racks “cleaner between cleanings” by inhibiting bacteria, mold, mildew and fungi that cause odors, stains and product degradation.
- **Versatile:** Racks join together easily without tools in “end-to-end” and “back-to-back” configurations with the exclusive bow-tie™ feature.
- **Durable:** Rust and corrosion proof polymer construction.
- **Strong:** Heavy-duty construction gives racks the strength to hold up to 3,000 lbs. (1,365kg) per unit.
- **Unique Design:** Racks have front to back slots for easier loading and unloading and superior air flow which promotes longer shelf life.
- **NSF Listed**
- **UPS Shippable**
- **No Assembly Required.**



***Racks joined in  
“end-to-end” configuration.***

Metro® BOW-TIE™ DUNNAGE RACKS  
with \*Microban® Antimicrobial  
Product Protection



*Racks joined in “end-to-end”  
and “back-to-back” configuration.*

## Specifications

- Rotationally molded grey polyethylene construction
- Slotted top for air circulation
- Slots run front to back for easy loading and unloading
- All rack edges have generous radius to prevent product snagging or marking
- Weight capacity: 30" (762mm) and 36" (914mm) racks — 1,500 lbs. (683kg)  
48" (1219mm) and 60" (1524mm) racks — 3,000 lbs. (1365kg)
- Each rack provided with separate polymer tie for joining racks in “end-to-end”  
and “back-to-back” configurations. Rack has a recess centered each side of top  
surface to accept polymer tie.
- Joining system bow-tie drops in and is removed from top without the use of tools.

Cat. No.	Width		Length		Height		Approx. Pkg. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lb.)	(kg)
HP2230PDMB	22	559	30	762	12	305	24	10.9
HP2236PDMB	22	559	36	914	12	305	26	11.8
HP2248PDMB	22	559	48	1219	12	305	34	15.4
HP2260PDMB	22	559	60	1524	12	305	42	19