



TIM CAMPBELL 800-400-7500

Item # \_\_\_\_\_

Job \_\_\_\_\_

## ERECTA SHELF® SHELVING

- **Ease of Assembly:** Grooves on shelves position and lock shelves to the uprights. Unit is assembled in minutes. No nuts, bolts or special tools are required.
- **Unique Design:** The open wire construction of Erecta Shelf® minimizes dust accumulation and allows a free circulation of air, greater visibility of stored items and greater light penetration.
- **Versatile Construction:** Erecta Shelf® shelving changes as quickly as your needs change. By using various accessories, hundreds of shelving configurations become possible.
- **Uprights:** Consist of two vertical 1/4" (6mm) diameter outer wires on each side with #4 diameter support wires welded between each of the outer pair spaced at 5" (127mm) intervals. Diagonal wire provides additional support.
- **Adjustability:** Shelves can be placed at 5" (127mm) intervals along the upright.
- **Adjustable Feet:** Bolt levelers compensate for surface irregularities.
- **Shipped Knocked Down** to save freight costs.
- **Durable Chrome-Plated Finish.**





# ERECTA SHELF® SHELVING

## Specifications

Erecta Shelf meets Government Specifications:  
 IP/DES S-128-0 MIL-S-40144E, Federal Supply Catalog,  
 Department of Defense, Sec. C6-10-SL.  
 Stock No. 7125-706-4239  
 Stock No. 7125-707-3041

## Dimensions

### Shelves

Width		Length		Approx. Pkd. Wt.		Cat. No. Chrome
(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
12	305	24	610	5	2.3	1224C
12	305	30	760	6	2.7	1230C
12	305	36	910	7	3.2	1236C
12	305	42	1060	8 <sup>1</sup> / <sub>4</sub>	3.7	1242C
12	305	48	1220	9 <sup>1</sup> / <sub>2</sub>	4.3	1248C
12	305	60	1525	12	5.4	1260C
18	455	24	610	6 <sup>1</sup> / <sub>2</sub>	2.9	1824C
18	455	30	760	8	3.6	1830C
18	455	36	910	10	4.5	1836C
18	455	42	1060	11	5.0	1842C
18	455	48	1220	12 <sup>1</sup> / <sub>2</sub>	5.6	1848C
18	455	60	1525	16	7.3	1860C

24" (610mm) shelves assembled using two (2) 12" (305mm) shelves.

### Uprights

Width		Height		Approx. Pkd. Wt.		Cat. No. Chrome
(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
12	305	53 <sup>1</sup> / <sub>2</sub>	1360	7	3.2	1252C
12	305	63 <sup>1</sup> / <sub>2</sub>	1610	8	3.6	1262C
12	305	73 <sup>1</sup> / <sub>2</sub>	1870	9	4.0	1272C
12	305	88 <sup>1</sup> / <sub>2</sub>	2250	11	5.0	1287C
18	455	53 <sup>1</sup> / <sub>2</sub>	1360	8	3.6	1852C
18	455	63 <sup>1</sup> / <sub>2</sub>	1610	9	4.0	1862C
18	455	73 <sup>1</sup> / <sub>2</sub>	1870	11	5.0	1872C
18	455	88 <sup>1</sup> / <sub>2</sub>	2250	13 <sup>1</sup> / <sub>2</sub>	6.1	1887C

Uprights 24" (610mm) wide take 2 shelves 12" (305mm) wide.

**Load Rating:** Shelves up to 48" Long – 800 lbs. (363 kg) equally distributed.  
 Shelves 60" Long – 600 lbs. (277 kg) equally distributed.  
 Maximum – 2000 lbs. (907 kg) per 4 shelf unit.

**Important:** When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.