



TIM CAMPBELL 800-400-7500

Item # _____

Job _____

ERECTA SHELF® SHELVING

- **Ease of Assembly:** Grooves on shelves position and lock shelves to the uprights. Unit is assembled in minutes. No nuts, bolts or special tools are required.
- **Unique Design:** The open wire construction of Erecta Shelf® minimizes dust accumulation and allows a free circulation of air, greater visibility of stored items and greater light penetration.
- **Versatile Construction:** Erecta Shelf® shelving changes as quickly as your needs change. By using various accessories, hundreds of shelving configurations become possible.
- **Uprights:** Consist of two vertical 1/4" (6mm) diameter outer wires on each side with #4 diameter support wires welded between each of the outer pair spaced at 5" (127mm) intervals. Diagonal wire provides additional support.
- **Adjustability:** Shelves can be placed at 5" (127mm) intervals along the upright.
- **Adjustable Feet:** Bolt levelers compensate for surface irregularities.
- **Shipped Knocked Down** to save freight costs.
- **Durable Chrome-Plated Finish.**





ERECTA SHELF® SHELVING

Specifications

Erecta Shelf meets Government Specifications:
 IP/DES S-128-0 MIL-S-40144E, Federal Supply Catalog,
 Department of Defense, Sec. C6-10-SL.
 Stock No. 7125-706-4239
 Stock No. 7125-707-3041

Dimensions

Shelves

Width		Length		Approx. Pkd. Wt.		Cat. No. Chrome
(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
12	305	24	610	5	2.3	1224C
12	305	30	760	6	2.7	1230C
12	305	36	910	7	3.2	1236C
12	305	42	1060	8 ¹ / ₄	3.7	1242C
12	305	48	1220	9 ¹ / ₂	4.3	1248C
12	305	60	1525	12	5.4	1260C
18	455	24	610	6 ¹ / ₂	2.9	1824C
18	455	30	760	8	3.6	1830C
18	455	36	910	10	4.5	1836C
18	455	42	1060	11	5.0	1842C
18	455	48	1220	12 ¹ / ₂	5.6	1848C
18	455	60	1525	16	7.3	1860C

24" (610mm) shelves assembled using two (2) 12" (305mm) shelves.

Uprights

Width		Height		Approx. Pkd. Wt.		Cat. No. Chrome
(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	
12	305	53 ¹ / ₂	1360	7	3.2	1252C
12	305	63 ¹ / ₂	1610	8	3.6	1262C
12	305	73 ¹ / ₂	1870	9	4.0	1272C
12	305	88 ¹ / ₂	2250	11	5.0	1287C
18	455	53 ¹ / ₂	1360	8	3.6	1852C
18	455	63 ¹ / ₂	1610	9	4.0	1862C
18	455	73 ¹ / ₂	1870	11	5.0	1872C
18	455	88 ¹ / ₂	2250	13 ¹ / ₂	6.1	1887C

Uprights 24" (610mm) wide take 2 shelves 12" (305mm) wide.

Load Rating: Shelves up to 48" Long – 800 lbs. (363 kg) equally distributed.
 Shelves 60" Long – 600 lbs. (277 kg) equally distributed.
 Maximum – 2000 lbs. (907 kg) per 4 shelf unit.

Important: When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.