



TIM CAMPBELL 800-400-7500

Item # \_\_\_\_\_

Job \_\_\_\_\_

## METRO® MOBILE END LOAD “KNOCK DOWN” RACKS

- **Material:** Special design, natural finish, high-strength, extruded aluminum (6063-T6 alloy).
- **Rugged:** Tubular framework with aircraft-riveted slide assemblies.
- **Economical:** Shipped “knocked down” for reduced freight rate. Easily assembled with 12 bolts.
- **Sanitary:** Removable slide assemblies for easy cleaning.
- **Versatile:** Slide assemblies can be replaced with slides of other than standard spacing while retaining the same framework.
- **Pass-Thru Design:** Can be loaded on one side and unloaded from the other for maximum efficiency and convenience.
- **Stable:** 5" (127mm) diameter, NSF-listed casters, corner-mounted for maximum stability.
- **Lightweight:** Easy to handle.
- **Rapid Cooling**

**NOTE:** Available factory set-up. See price list.






# METRO® MOBILE END LOAD “KNOCK DOWN” RACKS

## Specifications

- **Material:** Special design, natural finish, high strength, extruded aluminum (6063-T6 alloy).
- **Construction:** Pass-thru design, aircraft-riveted construction on slide assemblies, tensilok fasteners for frame assembly.
- **End Frames:** 1" square x .093" (25x2.4mm) wall extruded aluminum tubing.
- **Tie Bars:** Left to right and front to back tie bars of 1" (25mm) diameter aluminum bar stock, drilled and tapped at each end.
- **Slides, 3" & 5" (75 & 127mm) Spacing:** .060"x1 1/4"x1 1/2" (1.5x32x38mm) profile, bulb-tipped extruded angle-riveted to .060"x1"x1" (1.5x25x25mm) angle uprights.
- **Slides, 1 1/2" (38mm) Spacing:** .060"x1/2"x1 1/2" (1.5x12.7x38mm) bulb-tipped, extruded channel-riveted to .060"x1"x1" (1.5x25x25mm) angle uprights.
- **Casters:** Two HS5M on back — 5" (127mm) diameter ball bearing swivel stem casters with self-lubricating axle. Two HS5MB on front — same as above with wheel brake. NSF listed.
- **Load Rating:** 20 lbs. (9kg) per level. Not to exceed 350 lbs. (159kg) per unit.



## Dimensions

Cat. No.	(a) (b) (c) Height/Width/Depth		(d) Inside Height		Slide Spacing		Pan Capacity		Shipping Weight	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	No.	Size (in.)	(lbs.)	(kg)
RT183N	64 1/8 x 20 3/8 x 28	1630 x 520 x 710	55 7/8	1420	3	76 or 36	18 14 x 18	18 x 26	53	24
RT115N	64 1/8 x 20 3/8 x 28	1630 x 520 x 710	55 7/8	1420	5	127 or 22	11 14 x 18	18 x 26	50	23
RT1334N	64 1/8 x 20 3/8 x 28	1630 x 520 x 710	55 7/8	1420	1 1/2	38	34	18 x 26	55	25

## Accessories

Model	Description
SU	Factory Set-Up
A38	Gray Rubber Corner Bumpers